



HIPERDRAI V

FAST MORTAR TO SEAL OFF LEAKS

Compound of special cements and chloride exempt additives specially formulated for emergency anchorages and repairings.

USES

The product is usually used to repair water pipes and tanks, basements, lift hollows, filtration through the rocks, fissures, new buildings settling movements, etc. Due to its high initial and final resistance it is ideal for fast and sure anchorages and to stop continuous water leakings.

SURFACE PREPARATION

The surface must be clean and free of paints, greases, oils, dust, etc. and it has also to be firm and hard. The surfaces to waterproof must be PERFECTLY WET when HIPERDRAI-V is applied to achieve a perfect anchorage.

INSTRUCTIONS FOR USE

Put mixing water in a appropriate recipient and add HIPERDRAI-V until you obtain a consistent and plastic paste which must be used immediately. If you want to seal off a leak mix the desired amount of the product and apply the mixture on the water leaking PRESSING it with your hand or with a trowel. In case of big reparations, apply the mixture in several steps. When there is high water pressure it will be necessary to make a discharge hole which will be closed finally with HIPERDRAI-V. Once the problem has been repaired and the mortar is cool, it is necessary to coat the zone with HIPERDRAI with the repaired surface previously wet. To apply the product below 5°C it is suitable to warm the water for the mixture.



CONSUMPTION

It will depend on each case, because it will vary depending on the wideness of the surface to repair and the water pressure.

COLOUR

Grey.

PACKING AND STORING

HIPERDRAI-V is packed in hermetic bags of 5 and 30 Kg., according to EC packing and storing directives for chemical products.

HYGIENE AND SAFETY

See product label.



Specifications		
Aspect:	Granulated grey powder	
Apparent density at 20°:	1,20 ± 0,05 g/cm ³	
Compression resistance UNE 83.821-92: 3,6 liters of water / 25 Kg of mortar		
1 Day	7 Days	28 days
84 Kg/cm ²	23 Kg/cm ²	240 Kg/cm ²