



DESMOL ESPECIAL

WOOD AND METALLIC PLANK MOULD REMOVER, EMULSIFIABLE WITH WATER

Desmol Especial is an effective plank mould remover in basis of refined mineral oils, emulsifiable with water and especially additvat.

PROPERTIES:

Excellent finished surface of cast.

Good performance of its high concentration.

Better durability of the moulds.

Avoid the adherence of plank mould concrete and column box.

USES

As cast and plank mould remover in structures and prefabricated concrete pieces, metallic moulds and wood.

SURFACE PREPARATION

The mould or the piece of column box must be clean and free of waste (concrete, mortars, med plaster, etc.)

INSTRUCTIONS FOR USE

DESMOL ESPECIAL can be applied by spraying, paintbrush, roller, broom, brush or immersion.



CONSUMPTION

DESMOL ESPECIAL is used by emulsion in water till 1/8 as maximum. Yield from 10 to 15 m² per liter of the product.

COLOUR

Amber.

PACKING AND STORING

DESMOL ESPECIAL is presented in hermetic barrels, according to EC packing and storing directives for chemical products.

HYGIENE AND SAFETY

See product label.



SPECIFICATIONS	
Main function:	Plank mould remover
Aspect:	Transparent liquid
Colour:	Amber
Stability:	Emulsión (20%) : 2 hours
Density:	0,90 g/cm ³
Viscosity (Copa Ford nº 4, 20°C):	30"
Active matter:	85%
Solubility:	Emulsionable in water