

BLUEFIX

BLUE ALIGNMENT FIXER

Elaborated with synthetic resins, exempt from solvents and is compatible to any type of surfaces. The particular size of its particles, bestow the high power of penetration to the surfaces of concrete and mortars, acting as an excellent alignment fixer, without forming a film.

USES

BLUEFIX is an excellent blue fixer, ideal for the protection during all work alignment carry out with ruling pen.

SURFACE PREPARATION

The surfaces must be clean, dry, and free of grease, oils or any other contaminants that may effect the penetration of the product on the surface.

INSTRUCTIONS FOR USE

For its application, sprinkle with spray or sulphator, on the marked lines, and let it dry.



CONSUMPTION

BLUEFIX is applied by spray with a yield of 50ml approx. Average is 50-80 ml per 1l of product.

COLOUR

Blue.

PACKING AND STORING

BLUEFIX is presented in plastic barrels of 30 and 60 litres, according to EC packing and storing directives for chemical products.

HYGIENE AND SAFETY

See product label.

| SPECIFICATIONS | |
|----------------------------------|-------------------------------|
| Aspect: | Bluish liquid colour |
| Viscosity (Copa Ford N°2, 25°C): | 25" approx. |
| Density at 20°C: | 0,99 ± 0,02 g/cm ³ |
| PH: | 8,3 ± 0,8 |
| Dry-to-touch at 20°C | 15 minutes |
| Dry extract (auto, 120°C, sand): | 7 ± 1% |