



PROTECTOR M

HIDRÓFUGO TRANSPARENTE ESPECIAL PARA MORTEROS MONOCAPA

Colorless water-repellent especially designed for the treatment over one layer cements, cements based in lime, stuccoed or other plaster finishes. Made of organic resins, steady and resistant to ultraviolet rays and highly resistant to chemical contaminants in the atmosphere.

Excellent water and dirt repellent without minimizing permeability of the water steam.

QUALITYS:

- The appearance of the surface maintains unalterable, that is because PROTECTOR M seeps in the base.
- Improves the aesthetic, avoiding the appearance of rashes.
- Cheap, one only application is needed.
- Easy to apply, its presented ready to use.
- In very cold zones protects surfaces from the freezing and thaw cycles.

USES

Especially specified for the process of hydrophobicity in all surfaces with porosity or semiporosity made of a one layer mortar, lime mortar, stuccoed, etc.

SURFACE PREPARATION

The support must be clean and dry.

In case of rashes, ask our Technical department.

If there are fissures or cracks, repair them before the application of the product.

INSTRUCTIONS FOR USE

PROTECTOR M, must be applied pure, with brush, paint roller or an low pressure airgun. One only plentiful layer must be applied, from the bottom to the top, to avoid unimpregnated zones.

CONSUMPTION

3-5 m² per liter. It depends on the capacity of absorption and roughness of the support, as well as how it's applied.

In case of doubt of the consume in very precise applications, it is recommended to make previous test.

COLOUR

Milky white.

PACKING AND STORING

PROTECTOR M is packed in hermetic barrels, according to EC packing and storing directives for chemical products.

HYGIENE AND SAFETY

See the product label.
Professional use.

SPECIFICATIONS	
Aspect:	Milky emulsion
Solids in weight:	28% ± 1%
Density:	1,02 ± 0,03 g/ml
Viscosity (Brookfield):	1000 ± 100 Cps
Stability on cold:	OK
Thermal stability:	OK
Mechanical stability:	OK
TMFF:	20 °C
pH:	9 ± 0,5